

## Nickel-Metal Hydride Rechargeable Battery



### Key Features

- NiMH 2700 mA·h
- 14.4 volts
- 38.88 Wh
- 12 AA cells with thermal control
- Insulated with 0.25 mm thick fish paper and PVC shrink wrap
- Molex, Mini-Fit Jr. connector
- 5.5 in. (13.97 cm) lead

### Specifications

Dimensions	2.15 x 0.58 x 6.78 in. (5.46 x 1.47 x 17.22 cm)
Weight	13.5 oz. (384 g)
Operating Temp.	-10°C to +55°C
Storage Temp.	-20°C to +30°C
Charging Temp.	0°C to +45°C
<b>CE</b> Complies with all applicable EU directives.	
Ordering Information	MOHR Part Number: CT100-AC-B2700

### Charging

The battery will automatically charge whenever the CT100B is plugged into an AC power source. Allow up to 4 hours for recharging when the battery is fully drained or when bringing the CT100B out of long-term storage.

### Storage conditions

Avoid direct sunlight, high temperature, and high humidity. Store in a cool place (temperature: -20°C to +30°C, humidity: from 40% to 80%).

### Environmental effects

Since a battery cell remains in the environment, do not throw it out into the environment. Recycle the battery through a recycling company.